




Engineering data		Mechanical data	
Ratio	8	Radial force for 20'000h	1050 N*
Number of stages	1	Radial force for 30'000h	900 N*
Rated output torque	15 Nm	Max. radial force	1650 N*
Cycling output torque	18 Nm	Axial force for 20'000h	1350 N
Max output torque	28 Nm	Axial force for 30'000h	1000 N
Emergency output torque	80 Nm	Max. axial force	2100 N
Rated input speed	4500 rpm	Protection	IP54
Max input speed	13000 rpm	Input inertia	0.07 kgcm ²
Efficiency	96 %*	Mass	1.42 kg
Operating temperature	<-25; 90> °C	Tilting moment for 20'000h	42 Nm
Backlash	< 10 arcmin	Tilting moment for 30'000h	36 Nm
Service life	20000 h	Max. bending moment	12 Nm
Running noise	58 dB(A)	Output shaft design	Smooth shaft
Torsional stiffness	5.60 Nm/arcmin		

* at rated speed & torque

* Defined for point of action at ½ output shaft length

Lubrication		Supported motors	
Type	Standard	Motor types	TGN2, TGT2, TGH2
Lubricant	Grease (lifetime lubrication)	Clamping diameter	11 mm
Customs info		Input flange	Motor adaptation - one part
HS Code	84834090	Installation position	Any



NO OF STAGES	K	K1
I. stage	111	51
II. stage	124	64

INDEX	ZMĚNA	DATUM	PODPIS		
ZM.MAT.			T.O.	HMOTNOST kg	MĚŘ.
ROZM.-POLOT.				ČSN	TR.Č.
ROZM. ZAŘ.				POZN.	Č. KUSOVNÍKU
VYPR.	NORM. REF.			STARÝ V.	Č.V.
PŘEKR.					
TECHNOL.	SCHVÁLIL.	12.9.2020			
NÁZEV	Gearbox SG070			TGN2, TGH2, TGT2	
				Lístů	List