




Engineering data		Mechanical data	
Ratio	8	Radial force for 20'000h	1900 N*
Number of stages	1	Radial force for 30'000h	1700 N*
Rated output torque	42 Nm	Max. radial force	3100 N*
Cycling output torque	50 Nm	Axial force for 20'000h	2000 N
Max output torque	80 Nm	Axial force for 30'000h	1500 N
Emergency output torque	190 Nm	Max. axial force	3800 N
Rated input speed	4000 rpm	Protection	IP54
Max input speed	7000 rpm	Input inertia	0.39 kgcm ²
Efficiency	97 %*	Mass	3.28 kg
Operating temperature	<-25; 90> °C	Tilting moment for 20'000h	99 Nm
Backlash	< 7 arcmin	Tilting moment for 30'000h	89 Nm
Service life	20000 h	Max. bending moment	16 Nm
Running noise	60 dB(A)	Output shaft design	Smooth shaft
Torsional stiffness	12.00 Nm/arcmin		

* at rated speed & torque

* Defined for point of action at ½ output shaft length

Lubrication		Supported motors	
Type	Standard	Motor types	TGN3, TGT3, TGH3
Lubricant	Grease (lifetime lubrication)	Clamping diameter	19 mm
Customs info		Input flange	Motor adaptation - one part
HS Code	84834090	Installation position	Any



NO OF STAGES	K	K1
I. stage	147	67,5
II. stage	164,5	85

INDEX	ZMĚNA	DATUM	PODPIS		
ZM.MAT.				HMOTNOST kg	MĚŘ.
ROZM.-POLOT.				ČSN	TR.Č.
ROZM. ZAŘ.				POZN.	Č. KUSOVNÍKU
VYPR.	NORM. REF.			STARÝ V.	Č.V.
PŘEKR.					
TECHNOL.	SCHVÁLIL.	12.9.2020			
NÁZEV	Gearbox SG090			TGN3, TGH3, TGT3	
				Listů	List