


Engineering data		Mechanical data	
Ratio	80	Radial force for 20'000h	750 N*
Number of stages	3	Radial force for 30'000h	650 N*
Rated output torque	102 Nm	Max. radial force	1250 N*
Cycling output torque	120 Nm	Axial force for 20'000h	1000 N
Max output torque	192 Nm	Axial force for 30'000h	900 N
Emergency output torque	240 Nm	Max. axial force	1600 N
Rated input speed	4000 rpm	Protection	IP54
Max input speed	7000 rpm	Input inertia	0.40 kgcm ²
Efficiency	91 %*	Mass	3.06 kg
Operating temperature	<-25; 90> °C	Tilting moment for 20'000h	31 Nm
Backlash	< 11 arcmin	Tilting moment for 30'000h	27 Nm
Service life	20000 h	Max. bending moment	16 Nm
Running noise	60 dB(A)	Output shaft design	Shaft key
Torsional stiffness	10.20 Nm/arcmin		

* at rated speed & torque

* Defined for point of action at ½ output shaft length

Lubrication		Supported motors	
Type	Standard	Motor types	TGN3, TGT3, TGH3
Lubricant	Grease (lifetime lubrication)	Clamping diameter	19 mm
Customs info		Input flange	Motor adaptation - one part
HS Code	84834090	Installation position	Any



NO OF STAGES	K	K1
I. stage	133,5	60
II. stage	151	77,5
III. stage	168,5	95

INDEX			DATA	PODPIS		
ZMĚNA						
ZM.MAT.				T.O.	HMOTNOST kg	MĚŘ.
ROZM.-POLOT.						
ROZM. ZAŘ.				ČSN	TRČ.	
VYPR.		NORM. REF.		POZN.	Č. KUSOVNÍKU	
PŘEKR.						
TECHNOL.		SCHVÁLIL.	12.9.2020	STARÝ V.	Č.V.	
NÁZEV				TGN3, TGH3, TGT3		
Gearbox SG080				Listů	List	