


Engineering data		Mechanical data	
Ratio	5	Radial force for 20'000h	1900 N*
Number of stages	1	Radial force for 30'000h	1700 N*
Rated output torque	63 Nm	Max. radial force	3100 N*
Cycling output torque	82 Nm	Axial force for 20'000h	2000 N
Max output torque	131 Nm	Axial force for 30'000h	1500 N
Emergency output torque	220 Nm	Max. axial force	3800 N
Rated input speed	4000 rpm	Protection	IP54
Max input speed	7000 rpm	Input inertia	0.48 kgcm ²
Efficiency	98 %*	Mass	3.27 kg
Operating temperature	<-25; 90> °C	Tilting moment for 20'000h	99 Nm
Backlash	< 7 arcmin	Tilting moment for 30'000h	89 Nm
Service life	20000 h	Max. bending moment	16 Nm
Running noise	60 dB(A)	Output shaft design	Shaft key
Torsional stiffness	12.00 Nm/arcmin		

* at rated speed & torque

* Defined for point of action at ½ output shaft length

Lubrication		Supported motors	
Type	Standard	Motor types	TGN3, TGT3, TGH3
Lubricant	Grease (lifetime lubrication)	Clamping diameter	19 mm
Customs info		Input flange	Motor adaptation - one part
HS Code	84834090	Installation position	Any



NO OF STAGES	K	K1
I. stage	147	67,5
II. stage	164,5	85

INDEX	ZMĚNA	DATA	PODPIS		
ZM.MAT.			T.O.	HMOTNOST kg	MĚŘ.
ROZM.-POLOT.					
ROZM. ZAŘ.				ČSN	TRČ.
VYPR.		NORM. REF.		POZN.	Č. KUSOVNÍKU
PŘEKR.					
TECHNOL.		SCHVÁLIL.	12.9.2020	STARÝ V.	Č.V.
NÁZEV					
Gearbox SG090				TGN3, TGH3, TGT3	
				Listů	Listů