


Engineering data		Mechanical data	
Ratio	3	Radial force for 20'000h	1750 N*
Number of stages	1	Radial force for 30'000h	1500 N*
Rated output torque	97 Nm	Max. radial force	2000 N*
Cycling output torque	115 Nm	Axial force for 20'000h	2500 N
Max output torque	184 Nm	Axial force for 30'000h	2100 N
Emergency output torque	375 Nm	Max. axial force	3800 N
Rated input speed	2150 rpm	Protection	IP54
Max input speed	6500 rpm	Input inertia	2.36 kgcm ²
Efficiency	98 %*	Mass	5.67 kg
Operating temperature	<-25; 90> °C	Tilting moment for 20'000h	101 Nm
Backlash	< 7 arcmin	Tilting moment for 30'000h	86 Nm
Service life	20000 h	Max. bending moment	40 Nm
Running noise	65 dB(A)	Output shaft design	Shaft key
Torsional stiffness	21.00 Nm/arcmin		

* at rated speed & torque

* Defined for point of action at ½ output shaft length

Lubrication		Supported motors	
Type	Standard	Motor types	TGN5, TGT5, TGH5
Lubricant	Grease (lifetime lubrication)	Clamping diameter	24 mm
Customs info		Input flange	Motor adaptation - one part
HS Code	84834090	Installation position	Any



NO OF STAGES	K	K1
I. stage	186,5	74
II. stage	214	101,5
III. stage	241,5	129

INDEX	ZMĚNA	DATUM	PODPIS		
ZM.MAT.			T.O.	HMOTNOST kg	MĚŘ.
ROZM.-POLOT.				ČSN	TRČ.
ROZM. ZAŘ.				POZN.	Č. KUSOVNÍKU
VYPR.	NORM. REF.			STARÝ V.	Č.V.
PŘEKR.					
TECHNOL.	SCHVÁLIL.	12.9.2020			
NÁZEV	Gearbox SG115			TGN5, TGH5, TGT5	
Listů				List	