

| Engineering data        |                 | Mechanical data            |                        |
|-------------------------|-----------------|----------------------------|------------------------|
| Ratio                   | 4               | Radial force for 20'000h   | 5200 N*                |
| Number of stages        | 1               | Radial force for 30'000h   | 4600 N*                |
| Rated output torque     | 390 Nm          | Max. radial force          | 8400 N*                |
| Cycling output torque   | 460 Nm          | Axial force for 20'000h    | 7000 N                 |
| Max output torque       | 600 Nm          | Axial force for 30'000h    | 6000 N                 |
| Emergency output torque | 920 Nm          | Max. axial force           | 11000 N                |
| Rated input speed       | 1400 rpm        | Protection                 | IP54                   |
| Max input speed         | 5500 rpm        | Input inertia              | 7.61 kgcm <sup>2</sup> |
| Efficiency              | 98 %*           | Mass                       | 16.61 kg               |
| Operating temperature   | <-25; 90> °C    | Tilting moment for 20'000h | 497 Nm                 |
| Backlash                | < 6 arcmin      | Tilting moment for 30'000h | 440 Nm                 |
| Service life            | 20000 h         | Max. bending moment        | 180 Nm                 |
| Running noise           | 70 dB(A)        | Output shaft design        | Smooth shaft           |
| Torsional stiffness     | 71.00 Nm/arcmin |                            |                        |

\* at rated speed & torque

\* Defined for point of action at ½ output shaft length

| Lubrication  |                               | Supported motors      |                             |
|--------------|-------------------------------|-----------------------|-----------------------------|
| Type         | Standard                      | Motor types           | TGN5, TGT5, TGH5            |
| Lubricant    | Grease (lifetime lubrication) | Clamping diameter     | 35 mm                       |
| Customs info |                               | Input flange          | Motor adaptation - one part |
| HS Code      | 84834090                      | Installation position | Any                         |

