

Engineering data		Mechanical data	
Ratio	5	Radial force for 20'000h	5200 N*
Number of stages	1	Radial force for 30'000h	4600 N*
Rated output torque	375 Nm	Max. radial force	8400 N*
Cycling output torque	445 Nm	Axial force for 20'000h	7000 N
Max output torque	710 Nm	Axial force for 30'000h	6000 N
Emergency output torque	890 Nm	Max. axial force	11000 N
Rated input speed	1600 rpm	Protection	IP54
Max input speed	5500 rpm	Input inertia	6.48 kgcm ²
Efficiency	98 %*	Mass	16.64 kg
Operating temperature	<-25; 90> °C	Tilting moment for 20'000h	497 Nm
Backlash	< 6 arcmin	Tilting moment for 30'000h	440 Nm
Service life	20000 h	Max. bending moment	180 Nm
Running noise	70 dB(A)	Output shaft design	Shaft key
Torsional stiffness	71.00 Nm/arcmin		

* at rated speed & torque

* Defined for point of action at ½ output shaft length

Lubrication		Supported motors	
Type	Standard	Motor types	TGN6, TGT6
Lubricant	Grease (lifetime lubrication)	Clamping diameter	35 mm
Customs info		Input flange	Motor adaptation - one part
HS Code	84834090	Installation position	Any

