

Engineering data		Mechanical data	
Ratio	7	Radial force for 20'000h	2150 N
Number of stages	1	Radial force for 30'000h	1900 N
Rated output torque	22 Nm	Max. radial force	2150 N
Cycling output torque	39 Nm	Axial force for 20'000h	4300 N
Max output torque	59 Nm	Axial force for 30'000h	3800 N
Emergency output torque	90 Nm	Max. axial force	4300 N
Rated input speed	3200 rpm	Protection	IP65
Max input speed	14000 rpm	Input inertia	0.23 kgcm ²
Efficiency	95 %*	Mass	1.33 kg
Operating temperature	<-25; 90> °C	Tilting moment for 20'000h	132 Nm
Backlash	< 2 arcmin	Tilting moment for 30'000h	117 Nm
Service life	20000 h	Max. bending moment	18 Nm
Running noise	60 dB(A)		
Torsional stiffness	13.20 Nm/arcmin		

* at rated speed & torque

Lubrication	
Type	Standard
Lubricant	Castrol Optigear Synthetic 800/150

Customs info	
HS Code	84834090

Output shaft design Flange with dowel hole

Supported motors	
Motor types	TGN3, TGT3, TGH3
Clamping diameter	14 mm
Input flange	Motor adaptation - 2 part, round universal flange
Installation position	Any

