

Engineering data		Mechanical data	
Ratio	16	Radial force for 20'000h	12000 N
Number of stages	2	Radial force for 30'000h	11000 N
Rated output torque	500 Nm	Max. radial force	12000 N
Cycling output torque	1000 Nm	Axial force for 20'000h	8500 N
Max output torque	1230 Nm	Axial force for 30'000h	7500 N
Emergency output torque	2000 Nm	Max. axial force	8500 N
Rated input speed	1700 rpm	Protection	IP65
Max input speed	8500 rpm	Input inertia	2.78 kgcm ²
Efficiency	96 %*	Mass	14.81 kg
Operating temperature	<-25; 90> °C	Tilting moment for 20'000h	1219 Nm
Backlash	< 1 arcmin	Tilting moment for 30'000h	1117 Nm
Service life	20000 h	Max. bending moment	80 Nm
Running noise	70 dB(A)	Output shaft design	Flange
Torsional stiffness	223.00 Nm/arcmin		

* at rated speed & torque

Lubrication		Supported motors	
Type	Standard	Motor types	TGN5, TGT5, TGH5
Lubricant	Castrol Optigear Synthetic 800/150	Clamping diameter	24 mm
		Input flange	Motor adaptation - 2 part, round universal flange
Customs info		Installation position	Any
HS Code	84834090		

