

Engineering data		Mechanical data	
Ratio	5	Radial force for 20'000h	12000 N
Number of stages	1	Radial force for 30'000h	11000 N
Rated output torque	375 Nm	Max. radial force	12000 N
Cycling output torque	750 Nm	Axial force for 20'000h	8500 N
Max output torque	750 Nm	Axial force for 30'000h	7500 N
Emergency output torque	1420 Nm	Max. axial force	8500 N
Rated input speed	950 rpm	Protection	IP65
Max input speed	6500 rpm	Input inertia	9.73 kgcm ²
Efficiency	97 %*	Mass	12.75 kg
Operating temperature	<-25; 90> °C	Tilting moment for 20'000h	1219 Nm
Backlash	< 3 arcmin	Tilting moment for 30'000h	1117 Nm
Service life	20000 h	Max. bending moment	180 Nm
Running noise	70 dB(A)	Output shaft design	Flange with dowel hole
Torsional stiffness	211.00 Nm/arcmin		
* at rated speed & torque			
Lubrication		Supported motors	
Type	Standard	Motor types	TGN5, TGT5, TGH5
Lubricant	Castrol Optigear Synthetic 800/150	Clamping diameter	35 mm
Customs info		Input flange	Motor adaptation - 2 part, square universal flange
HS Code	84834090	Installation position	Any

