

Engineering data		Mechanical data	
Ratio	20	Radial force for 20'000h	4900 N
Number of stages	2	Radial force for 30'000h	4350 N
Rated output torque	150 Nm	Max. radial force	4900 N
Cycling output torque	300 Nm	Axial force for 20'000h	9500 N
Max output torque	480 Nm	Axial force for 30'000h	8400 N
Emergency output torque	650 Nm	Max. axial force	9500 N
Rated input speed	3750 rpm	Protection	IP65
Max input speed	10000 rpm	Input inertia	2.04 kgcm ²
Efficiency	96 %*	Mass	6.77 kg
Operating temperature	<-25; 90> °C	Tilting moment for 20'000h	475 Nm
Backlash	< 5 arcmin	Tilting moment for 30'000h	422 Nm
Service life	20000 h	Max. bending moment	38 Nm
Running noise	65 dB(A)	Output shaft design	Flange
Torsional stiffness	75.00 Nm/arcmin		

* at rated speed & torque

Lubrication		Supported motors	
Type	Standard	Motor types	TGN6, TGT6
Lubricant	Castrol Optigear Synthetic 800/150	Clamping diameter	24 mm
		Input flange	Motor adaptation - 2 part, round universal flange
Customs info		Installation position	Any
HS Code	84834090		

