

Engineering data		Mechanical data	
Ratio	25	Radial force for 20'000h	320 N*
Number of stages	2	Radial force for 30'000h	295 N*
Rated output torque	15 Nm	Max. radial force	520 N*
Cycling output torque	18 Nm	Axial force for 20'000h	620 N
Max output torque	28 Nm	Axial force for 30'000h	620 N
Emergency output torque	36 Nm	Max. axial force	620 N
Rated input speed	5000 rpm	Protection	IP54
Max input speed	18000 rpm	Input inertia	0.02 kgcm ²
Efficiency	92 %*	Mass	0.47 kg
Operating temperature	<-25; 90> °C	Tilting moment for 20'000h	8 Nm
Backlash	< 19 arcmin	Tilting moment for 30'000h	8 Nm
Service life	20000 h	Max. bending moment	4 Nm
Running noise	58 dB(A)	Output shaft design	Shaft key
Torsional stiffness	1.95 Nm/arcmin		

* at rated speed & torque

* Defined for point of action at ½ output shaft length

Lubrication		Supported motors	
Type	Standard	Motor types	TGN2, TGT2, TGH2
Lubricant	Grease (lifetime lubrication)	Clamping diameter	9 mm
Customs info		Input flange	Motor adaptation - one part
HS Code	84834090	Installation position	Any

