




Engineering data		Mechanical data	
Ratio	512	Radial force for 20'000h	320 N*
Number of stages	3	Radial force for 30'000h	295 N*
Rated output torque	6 Nm	Max. radial force	520 N*
Cycling output torque	7.5 Nm	Axial force for 20'000h	620 N
Max output torque	12 Nm	Axial force for 30'000h	620 N
Emergency output torque	27 Nm	Max. axial force	620 N
Rated input speed	5000 rpm	Protection	IP54
Max input speed	18000 rpm	Input inertia	0.02 kgcm ²
Efficiency	46 %*	Mass	0.57 kg
Operating temperature	<-25; 90> °C	Tilting moment for 20'000h	8 Nm
Backlash	< 22 arcmin	Tilting moment for 30'000h	8 Nm
Service life	20000 h	Max. bending moment	4 Nm
Running noise	58 dB(A)	Output shaft design	Shaft key
Torsional stiffness	2.10 Nm/arcmin		

* at rated speed & torque

* Defined for point of action at ½ output shaft length

Lubrication		Supported motors	
Type	Standard	Motor types	TGN2, TGT2, TGH2
Lubricant	Grease (lifetime lubrication)	Clamping diameter	9 mm
Customs info		Input flange	Motor adaptation - one part
HS Code	84834090	Installation position	Any



NO OF STAGES	K	K1
I. stage	85	35,5
II. stage	98	48,5
III. stage	110,5	61

INDEX	ZMĚNA	DATUM	PODPIS		
ZM.MAT.			T.O.	HMOTNOST kg	MĚŘ.
ROZM.-POLOT.				ČSN	TR.Č.
ROZM. ZAR.				POZN.	Č. KUSOVNÍKU
VYPR.	NORM. REF.			STARÝ V.	Č.V.
PŘEKR.					
TECHNOL.	SCHVÁLIL.	12.9.2020			
NÁZEV	Gearbox SGQ040			TGN2, TGH2, TGT2	
				Listů	List