

Engineering data		Mechanical data	
Ratio	100	Radial force for 20'000h	2500 N*
Number of stages	2	Radial force for 30'000h	2150 N*
Rated output torque	80 Nm	Max. radial force	4000 N*
Cycling output torque	95 Nm	Axial force for 20'000h	4000 N
Max output torque	152 Nm	Axial force for 30'000h	3000 N
Emergency output torque	480 Nm	Max. axial force	5900 N
Rated input speed	3500 rpm	Protection	IP54
Max input speed	6500 rpm	Input inertia	1.38 kgcm ²
Efficiency	83 %*	Mass	9.72 kg
Operating temperature	<-25; 90> °C	Tilting moment for 20'000h	168 Nm
Backlash	< 9 arcmin	Tilting moment for 30'000h	144 Nm
Service life	20000 h	Max. bending moment	40 Nm
Running noise	65 dB(A)	Output shaft design	Shaft key
Torsional stiffness	43.50 Nm/arcmin		

* at rated speed & torque

* Defined for point of action at ½ output shaft length

Lubrication		Supported motors	
Type	Standard	Motor types	TGN5, TGT5, TGH5
Lubricant	Grease (lifetime lubrication)	Clamping diameter	24 mm
Customs info		Input flange	Motor adaptation - one part
HS Code	84834090	Installation position	Any

