

Engineering data (WIN 1035)

DC bus voltage	48 V DC
Nominal AC voltage	33 V AC (rms)
Rated voltage	32 V AC (rms)
Rated power	286 W
Rated speed	3000 rpm
Rated torque	0.91 Nm
Rated current	7.31 A (rms)
Peak torque	3.77 Nm
Peak current	33.4 A (rms)
Stall torque	0.95 Nm
Stall current	7.3 A (rms)
No load speed	4180 rpm
EMF constant ±10%	7.8 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.13 Nm / A (rms)
Torque constant ±10% @ rated load	0.12 Nm / A (rms)
Number of poles	6
Electrical time constant	1.36 ms
Winding terminal resistance	0.87 Ω
Rotary field terminal inductance	1.18 mH

Customs info

HS Code	85015100
---------	----------


Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	1.00 ms
Thermal time constant	18 min
Rotor inertia	0.11 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	1.7 kg
Max. axial force 20kh	48 N
Max. radial force 20kh	254 N*
Max. axial force 100kh	28 N
Max. radial force 100kh	148 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EKM36 (HDSL) multi-turn, 17 + 12 bits


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

