

Engineering data (WIN 943)

DC bus voltage	320 V DC
Nominal AC voltage	220 V AC (rms)
Rated voltage	107 V AC (rms)
Rated power	471 W
Rated speed	9000 rpm
Rated torque	0.50 Nm
Rated current	2.97 A (rms)
Peak torque	3.8 Nm
Peak current	24 A (rms)
Stall torque	0.95 Nm
Stall current	5.2 A (rms)
No load speed	19950 rpm
EMF constant ±10%	11 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.18 Nm / A (rms)
Torque constant ±10% @ rated load	0.17 Nm / A (rms)
Number of poles	6
Electrical time constant	1.44 ms
Winding terminal resistance	1.6 Ω
Rotary field terminal inductance	2.3 mH

Customs info

HS Code	85015100
---------	----------


Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	0.92 ms
Thermal time constant	18 min
Rotor inertia	0.11 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	1.7 kg
Max. axial force 20kh	33 N
Max. radial force 20kh	176 N*
Max. axial force 100kh	20 N
Max. radial force 100kh	103 N*


* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EDM35 (HDSL) multi-turn, 20+12 bits


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

