


Engineering data (WIN 858)		Mechanical data (setting 48)	
DC bus voltage	560 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	0.93 ms
Rated voltage	276 V AC (rms)	Thermal time constant	18 min
Rated power	471 W	Rotor inertia	0.11 kgcm ²
Rated speed	6000 rpm	Protection	IP64
Rated torque	0.75 Nm	Color	RAL 9005
Rated current	1.21 A (rms)	Cooling	Convection
Peak torque	3.8 Nm	Motor-only mass	1.7 kg
Peak current	6.7 A (rms)	Max. axial force 20kh	40 N
Stall torque	0.95 Nm	Max. radial force 20kh	209 N*
Stall current	1.45 A (rms)	Max. axial force 100kh	23 N
No load speed	9580 rpm	Max. radial force 100kh	122 N*
EMF constant ±10%	39.5 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	0.65 Nm / A (rms)	Sensors	
Torque constant ±10% @ rated load	0.62 Nm / A (rms)	Temperature	PT1000 {PT1000}
Number of poles	6	Feedback	EKS36 (HDSL) single-turn, 17 bits
Electrical time constant	1.44 ms	Brake	
Winding terminal resistance	20.93 Ω	Braking torque	2.00 Nm
Rotary field terminal inductance	30.2 mH	Voltage	24 V DC
Customs info		Power @20°C	11.0 W
HS Code	85015100	Current @20°C	0.46 A
		Inertia	0.08 kgcm ²
		Mass	0.20 kg



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

