



Engineering data (WIN 811)		Mechanical data (setting 48)							
DC bus voltage	560 V DC	Max mechanical speed	12000 rpm						
Nominal AC voltage	380 V AC (rms)	Mech. time constant	1.09 ms						
Rated voltage	301 V AC (rms)	Thermal time constant	12 min						
Rated power	320 W	Rotor inertia	0.09 kgcm²						
Rated speed	4500 rpm	Protection	IP64						
Rated torque	0.68 Nm	Color	RAL 9005						
Rated current	0.83 A (rms)	Cooling	Convection						
Peak torque	3 Nm	Motor-only mass	0.9 kg						
Peak current	3.9 A (rms)	Max. axial force 20kh	41 N						
Stall torque	0.75 Nm	Max. radial force 20kh	215 N*						
Stall current	0.86 A (rms)	Max. axial force 100kh	24 N						
No load speed	7100 rpm	Max. radial force 100kh	126 N*						
EMF constant ±10%	53 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length							
Theoretical torque constant ±10%	0.88 Nm / A (rms)								
Torque constant ±10% @ rated load	0.82 Nm / A (rms)	<table><tr><th colspan="2">Sensors</th></tr><tr><td>Temperature</td><td>PT1000 {PT1000}</td></tr><tr><td>Feedback</td><td>EKS36 (HDSL) single-turn, 18 bits, SIL2</td></tr></table>		Sensors		Temperature	PT1000 {PT1000}	Feedback	EKS36 (HDSL) single-turn, 18 bits, SIL2
Sensors									
Temperature	PT1000 {PT1000}								
Feedback	EKS36 (HDSL) single-turn, 18 bits, SIL2								
Number of poles	6								
Electrical time constant	1.34 ms								
Winding terminal resistance	53.86 Ω								
Rotary field terminal inductance	72.1 mH								
Customs info									
HS Code	85015100								


EGA201N00000800000

M15, 9 poles, rotary


Connector 1 (304)

A	U
B	V
C	W
PE	PE
1	Brake+
2	Brake-
3	+Us/DSL+
4	GND/DSL-

