


Engineering data (WIN 811)		Mechanical data (setting 48)	
DC bus voltage	560 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	1.09 ms
Rated voltage	301 V AC (rms)	Thermal time constant	12 min
Rated power	320 W	Rotor inertia	0.09 kgcm ²
Rated speed	4500 rpm	Protection	IP64
Rated torque	0.68 Nm	Color	RAL 9005
Rated current	0.83 A (rms)	Cooling	Convection
Peak torque	3 Nm	Motor-only mass	1.35 kg
Peak current	3.9 A (rms)	Max. axial force 20kh	43 N
Stall torque	0.75 Nm	Max. radial force 20kh	227 N*
Stall current	0.86 A (rms)	Max. axial force 100kh	25 N
No load speed	7100 rpm	Max. radial force 100kh	133 N*
EMF constant ±10%	53 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	0.88 Nm / A (rms)	Sensors	
Torque constant ±10% @ rated load	0.82 Nm / A (rms)	Temperature	PT1000 {PT1000}
Number of poles	6	Feedback	EKM36 (HDSL) multi-turn, 17 + 12 bits
Electrical time constant	1.34 ms	Brake	
Winding terminal resistance	53.86 Ω	Braking torque	2.00 Nm
Rotary field terminal inductance	72.1 mH	Voltage	24 V DC
Customs info		Power @20°C	11.0 W
HS Code	85015100	Current @20°C	0.46 A
		Inertia	0.08 kgcm ²
		Mass	0.20 kg


EGA201N00000800000

M15, 9 poles, rotary


Connector 1 (304)

A	U
B	V
C	W
PE	PE
1	Brake+
2	Brake-
3	+Us/DSL+
4	GND/DSL-

