

Engineering data (WIN 1486)

DC bus voltage	24 V DC
Nominal AC voltage	17 V AC (rms)
Rated voltage	16 V AC (rms)
Rated power	160 W
Rated speed	3000 rpm
Rated torque	0.51 Nm
Rated current	9.01 A (rms)
Peak torque	1.79 Nm
Peak current	32.1 A (rms)
Stall torque	0.54 Nm
Stall current	8.9 A (rms)
No load speed	4560 rpm
EMF constant ±10%	3.65 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.06 Nm / A (rms)
Torque constant ±10% @ rated load	0.06 Nm / A (rms)
Number of poles	6
Electrical time constant	1.26 ms
Winding terminal resistance	0.438 Ω
Rotary field terminal inductance	0.55 mH

Customs info

HS Code	85015100
---------	----------


Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	1.46 ms
Thermal time constant	12 min
Rotor inertia	0.07 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	0.9 kg
Max. axial force 20kh	45 N
Max. radial force 20kh	234 N*
Max. axial force 100kh	26 N
Max. radial force 100kh	137 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EEM37 (HDSL) multi-turn, 17+12 bits



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

