

Engineering data (WIN 777)

DC bus voltage	36 V DC
Nominal AC voltage	25 V AC (rms)
Rated voltage	19 V AC (rms)
Rated power	160 W
Rated speed	3000 rpm
Rated torque	0.51 Nm
Rated current	7.65 A (rms)
Peak torque	2.08 Nm
Peak current	33.2 A (rms)
Stall torque	0.54 Nm
Stall current	7.6 A (rms)
No load speed	5710 rpm
EMF constant ±10%	4.3 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.07 Nm / A (rms)
Torque constant ±10% @ rated load	0.07 Nm / A (rms)
Number of poles	6
Electrical time constant	1.23 ms
Winding terminal resistance	0.62 Ω
Rotary field terminal inductance	0.76 mH

Customs info

HS Code	85015100
---------	----------


Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	1.49 ms
Thermal time constant	12 min
Rotor inertia	0.07 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	0.9 kg
Max. axial force 20kh	45 N
Max. radial force 20kh	234 N*
Max. axial force 100kh	26 N
Max. radial force 100kh	137 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EEM37 (HDSL) multi-turn, 17+12 bits


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

