

Engineering data (WIN 704)

DC bus voltage	320 V DC
Nominal AC voltage	220 V AC (rms)
Rated voltage	153 V AC (rms)
Rated power	597 W
Rated speed	3000 rpm
Rated torque	1.90 Nm
Rated current	3.06 A (rms)
Peak torque	6.15 Nm
Peak current	12.7 A (rms)
Stall torque	2.05 Nm
Stall current	2.79 A (rms)
No load speed	4920 rpm
EMF constant ±10%	44.5 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.74 Nm / A (rms)
Torque constant ±10% @ rated load	0.62 Nm / A (rms)
Number of poles	10
Electrical time constant	2.53 ms
Winding terminal resistance	5.26 Ω
Rotary field terminal inductance	13.3 mH

Customs info

HS Code	85015100
---------	----------


Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	0.92 ms
Thermal time constant	23 min
Rotor inertia	0.55 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	2 kg
Max. axial force 20kh	62 N
Max. radial force 20kh	327 N*
Max. axial force 100kh	36 N
Max. radial force 100kh	191 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EKM36 (HDSL) multi-turn, 17 + 12 bits



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

