

Engineering data (WIN 720)

DC bus voltage	560 V DC
Nominal AC voltage	380 V AC (rms)
Rated voltage	264 V AC (rms)
Rated power	1.6 kW
Rated speed	6000 rpm
Rated torque	2.50 Nm
Rated current	3.46 A (rms)
Peak torque	10.5 Nm
Peak current	15.3 A (rms)
Stall torque	3.5 Nm
Stall current	4.23 A (rms)
No load speed	7590 rpm
EMF constant ±10%	50 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.83 Nm / A (rms)
Torque constant ±10% @ rated load	0.72 Nm / A (rms)
Number of poles	10
Electrical time constant	2.88 ms
Winding terminal resistance	2.81 Ω
Rotary field terminal inductance	8.1 mH

Customs info

HS Code	85015220
---------	----------


Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	0.74 ms
Thermal time constant	27 min
Rotor inertia	1.04 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	2 kg
Max. axial force 20kh	54 N
Max. radial force 20kh	283 N*
Max. axial force 100kh	31 N
Max. radial force 100kh	165 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EKM36 (HDSL) multi-turn, 18+12 bits, SIL2


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

