

Engineering data (WIN 1057)

DC bus voltage	560 V DC
Nominal AC voltage	380 V AC (rms)
Rated voltage	258 V AC (rms)
Rated power	1.6 kW
Rated speed	6000 rpm
Rated torque	2.50 Nm
Rated current	4.12 A (rms)
Peak torque	14.4 Nm
Peak current	20 A (rms)
Stall torque	4.8 Nm
Stall current	5.6 A (rms)
No load speed	7300 rpm
EMF constant ±10%	52 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.86 Nm / A (rms)
Torque constant ±10% @ rated load	0.61 Nm / A (rms)
Number of poles	10
Electrical time constant	3.04 ms
Winding terminal resistance	1.91 Ω
Rotary field terminal inductance	5.8 mH

Customs info

HS Code	85015220
---------	----------


Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	0.68 ms
Thermal time constant	30 min
Rotor inertia	1.52 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	2 kg
Max. axial force 20kh	59 N
Max. radial force 20kh	311 N*
Max. axial force 100kh	35 N
Max. radial force 100kh	182 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EDS35 (HDSL) single-turn, 24 bits


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

