


Engineering data (WIN 1119)		Mechanical data (setting 48)	
DC bus voltage	320 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	220 V AC (rms)	Mech. time constant	0.68 ms
Rated voltage	113 V AC (rms)	Thermal time constant	30 min
Rated power	243 W	Rotor inertia	1.52 kgcm ²
Rated speed	500 rpm	Protection	IP64
Rated torque	4.65 Nm	Color	RAL 9005
Rated current	2.02 A (rms)	Cooling	Convection
Peak torque	14.4 Nm	Motor-only mass	2 kg
Peak current	7 A (rms)	Max. axial force 20kh	135 N
Stall torque	4.8 Nm	Max. radial force 20kh	713 N*
Stall current	1.96 A (rms)	Max. axial force 100kh	79 N
No load speed	1480 rpm	Max. radial force 100kh	417 N*
EMF constant ±10%	148 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	2.45 Nm / A (rms)		
Torque constant ±10% @ rated load	2.30 Nm / A (rms)	Sensors Temperature PT1000 {PT1000} Feedback EDS35 (HDSL) single-turn, 24 bits	
Number of poles	10		
Electrical time constant	3.01 ms		
Winding terminal resistance	15.48 Ω		
Rotary field terminal inductance	46.6 mH		
Customs info			
HS Code	85015100		


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

