


Engineering data (WIN 1312)		Mechanical data (setting 48)	
DC bus voltage	48 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	33 V AC (rms)	Mech. time constant	1.36 ms
Rated voltage	25 V AC (rms)	Thermal time constant	21 min
Rated power	465 W	Rotor inertia	0.31 kgcm ²
Rated speed	4000 rpm	Protection	IP64
Rated torque	1.11 Nm	Color	RAL 9005
Rated current	15.96 A (rms)	Cooling	Convection
Peak torque	3.45 Nm	Motor-only mass	2 kg
Peak current	61.6 A (rms)	Max. axial force 20kh	52 N
Stall torque	1.15 Nm	Max. radial force 20kh	272 N*
Stall current	14 A (rms)	Max. axial force 100kh	30 N
No load speed	6580 rpm	Max. radial force 100kh	159 N*
EMF constant ±10%	5 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	0.082 Nm / A (rms)	Sensors	
Torque constant ±10% @ rated load	0.070 Nm / A (rms)	Temperature	PT1000 {PT1000}
Number of poles	10	Feedback	EKM36 (HDSL) multi-turn, 18+12 bits, SIL2
Electrical time constant	2.25 ms	Brake	
Winding terminal resistance	0.173 Ω	Braking torque	4.50 Nm
Rotary field terminal inductance	0.39 mH	Voltage	24 V DC
Power @20°C		Current @20°C	12.0 W
Inertia		Mass	0.50 A
Mass			0.20 kgcm ²
			0.47 kg
Customs info			
HS Code	85015100		



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

