


Engineering data (WIN 787)		Mechanical data (setting 48)	
DC bus voltage	560 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	0.93 ms
Rated voltage	274 V AC (rms)	Thermal time constant	18 min
Rated power	401 W	Rotor inertia	0.11 kgcm²
Rated speed	4500 rpm	Protection	IP64
Rated torque	0.85 Nm	Color	RAL 9005
Rated current	1.07 A (rms)	Cooling	Convection
Peak torque	3.8 Nm	Motor-only mass	1.27 kg
Peak current	5.3 A (rms)	Max. axial force 20kh	42 N
Stall torque	0.95 Nm	Max. radial force 20kh	222 N*
Stall current	1.15 A (rms)	Max. axial force 100kh	25 N
No load speed	7560 rpm	Max. radial force 100kh	130 N*
EMF constant ±10%	50 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	0.83 Nm / A (rms)		
Torque constant ±10% @ rated load	0.79 Nm / A (rms)	Sensors Temperature PT1000 {PT1000} Feedback EKM36 (HDSL) multi-turn, 17 + 12 bits	
Number of poles	6		
Electrical time constant	1.44 ms		
Winding terminal resistance	33.57 Ω		
Rotary field terminal inductance	48.5 mH		
Customs info			
HS Code	85015100		


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

