

Engineering data (WIN 787)

DC bus voltage	560 V DC
Nominal AC voltage	380 V AC (rms)
Rated voltage	274 V AC (rms)
Rated power	401 W
Rated speed	4500 rpm
Rated torque	0.85 Nm
Rated current	1.07 A (rms)
Peak torque	3.8 Nm
Peak current	5.3 A (rms)
Stall torque	0.95 Nm
Stall current	1.15 A (rms)
No load speed	7560 rpm
EMF constant ±10%	50 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.83 Nm / A (rms)
Torque constant ±10% @ rated load	0.79 Nm / A (rms)
Number of poles	6
Electrical time constant	1.44 ms
Winding terminal resistance	33.57 Ω
Rotary field terminal inductance	48.5 mH

Customs info

HS Code	85015100
---------	----------

Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	0.93 ms
Thermal time constant	18 min
Rotor inertia	0.11 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	1.71 kg
Max. axial force 20kh	44 N
Max. radial force 20kh	230 N*
Max. axial force 100kh	26 N
Max. radial force 100kh	135 N*


* Defined for point of action at ½ output shaft length

Sensors


Temperature	PT1000 {PT1000}
Feedback	EDM35 (HDSL) multi-turn, 20+12 bits

Brake

Braking torque	2.00 Nm
Voltage	24 V DC
Power @20°C	11.0 W
Current @20°C	0.46 A
Inertia	0.08 kgcm ²
Mass	0.20 kg


EGA201N00000800000

M15, 9 poles, rotary


Connector 1 (304)

A	U
B	V
C	W
PE	PE
1	Brake+
2	Brake-
3	+Us/DSL+
4	GND/DSL-

