

Engineering data (WIN 778)

DC bus voltage	36 V DC
Nominal AC voltage	23 V AC (rms)
Rated voltage	16 V AC (rms)
Rated power	181 W
Rated speed	1500 rpm
Rated torque	1.15 Nm
Rated current	11.25 A (rms)
Peak torque	3.45 Nm
Peak current	44.2 A (rms)
Stall torque	1.15 Nm
Stall current	10 A (rms)
No load speed	3270 rpm
EMF constant ±10%	6.9 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.11 Nm / A (rms)
Torque constant ±10% @ rated load	0.10 Nm / A (rms)
Number of poles	10
Electrical time constant	2.21 ms
Winding terminal resistance	0.34 Ω
Rotary field terminal inductance	0.75 mH

Customs info

HS Code	85015100
---------	----------


Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	1.40 ms
Thermal time constant	21 min
Rotor inertia	0.31 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	15 kg
Max. axial force 20kh	68 N
Max. radial force 20kh	357 N*
Max. axial force 100kh	40 N
Max. radial force 100kh	209 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EDM35 (HDSL) multi-turn, 20+12 bits



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

