

Engineering data (WIN 1630)

DC bus voltage	560 V DC
Nominal AC voltage	380 V AC (rms)
Rated voltage	279 V AC (rms)
Rated power	1.1 kW
Rated speed	6000 rpm
Rated torque	1.80 Nm
Rated current	2.79 A (rms)
Peak torque	8.4 Nm
Peak current	14.1 A (rms)
Stall torque	2.8 Nm
Stall current	3.64 A (rms)
No load speed	8150 rpm
EMF constant ±10%	46.5 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.769 Nm / A (rms)
Torque constant ±10% @ rated load	0.645 Nm / A (rms)
Number of poles	10
Electrical time constant	2.53 ms
Winding terminal resistance	3.48 Ω
Rotary field terminal inductance	8.8 mH

Customs info

HS Code	85015220
---------	----------

Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	0.82 ms
Thermal time constant	25 min
Rotor inertia	0.8 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	3.2 kg
Max. axial force 20kh	63 N
Max. radial force 20kh	332 N*
Max. axial force 100kh	37 N
Max. radial force 100kh	194 N*


* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EKS36 (HDSL) single-turn, 17 bits

Brake

Braking torque	4.50 Nm
Voltage	24 V DC
Power @20°C	12.0 W
Current @20°C	0.50 A
Inertia	0.20 kgcm ²
Mass	0.47 kg


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

