

Engineering data (WIN 719)

DC bus voltage	560 V DC
Nominal AC voltage	380 V AC (rms)
Rated voltage	269 V AC (rms)
Rated power	635 W
Rated speed	6000 rpm
Rated torque	1.01 Nm
Rated current	1.99 A (rms)
Peak torque	3.45 Nm
Peak current	7.8 A (rms)
Stall torque	1.15 Nm
Stall current	1.78 A (rms)
No load speed	9680 rpm
EMF constant ±10%	39 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.65 Nm / A (rms)
Torque constant ±10% @ rated load	0.51 Nm / A (rms)
Number of poles	10
Electrical time constant	2.15 ms
Winding terminal resistance	10.71 Ω
Rotary field terminal inductance	23 mH

Customs info

HS Code	85015100
---------	----------


Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	1.38 ms
Thermal time constant	21 min
Rotor inertia	0.31 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	1.5 kg
Max. axial force 20kh	43 N
Max. radial force 20kh	225 N*
Max. axial force 100kh	25 N
Max. radial force 100kh	131 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EKM36 (HDSL) multi-turn, 18+12 bits, SIL2



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

