

Engineering data (WIN 739)

DC bus voltage	320 V DC
Nominal AC voltage	220 V AC (rms)
Rated voltage	193 V AC (rms)
Rated power	942 W
Rated speed	3000 rpm
Rated torque	3.00 Nm
Rated current	3.47 A (rms)
Peak torque	10.5 Nm
Peak current	12.3 A (rms)
Stall torque	3.5 Nm
Stall current	3.41 A (rms)
No load speed	3540 rpm
EMF constant ±10%	62 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	1.03 Nm / A (rms)
Torque constant ±10% @ rated load	0.86 Nm / A (rms)
Number of poles	10
Electrical time constant	2.86 ms
Winding terminal resistance	4.27 Ω
Rotary field terminal inductance	12.2 mH

Customs info

HS Code	85015220
---------	----------


Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	0.73 ms
Thermal time constant	27 min
Rotor inertia	1.04 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	2 kg
Max. axial force 20kh	68 N
Max. radial force 20kh	356 N*
Max. axial force 100kh	40 N
Max. radial force 100kh	208 N*


* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EDM35 (HDSL) multi-turn, 20+12 bits


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

