


Engineering data (WIN 783)		Mechanical data (setting 48)							
DC bus voltage	36 V DC	Max mechanical speed	12000 rpm						
Nominal AC voltage	25 V AC (rms)	Mech. time constant	0.99 ms						
Rated voltage	18 V AC (rms)	Thermal time constant	23 min						
Rated power	209 W	Rotor inertia	0.55 kgcm²						
Rated speed	1000 rpm	Protection	IP64						
Rated torque	2.00 Nm	Color	RAL 9005						
Rated current	11.02 A (rms)	Cooling	Convection						
Peak torque	6.15 Nm	Motor-only mass	1.5 kg						
Peak current	41.9 A (rms)	Max. axial force 20kh	90 N						
Stall torque	2.05 Nm	Max. radial force 20kh	472 N*						
Stall current	10.3 A (rms)	Max. axial force 100kh	52 N						
No load speed	2060 rpm	Max. radial force 100kh	276 N*						
EMF constant ±10%	12 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length							
Theoretical torque constant ±10%	0.2 Nm / A (rms)								
Torque constant ±10% @ rated load	0.2 Nm / A (rms)	<table><tr><th colspan="2">Sensors</th></tr><tr><td>Temperature</td><td>PT1000 {PT1000}</td></tr><tr><td>Feedback</td><td>EEM37 (HDSL) multi-turn, 17+12 bits</td></tr></table>		Sensors		Temperature	PT1000 {PT1000}	Feedback	EEM37 (HDSL) multi-turn, 17+12 bits
Sensors									
Temperature	PT1000 {PT1000}								
Feedback	EEM37 (HDSL) multi-turn, 17+12 bits								
Number of poles	10								
Electrical time constant	2.44 ms								
Winding terminal resistance	0.41 Ω								
Rotary field terminal inductance	1 mH								

Customs info	
HS Code	85015100


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

