


Engineering data (WIN 719)		Mechanical data (setting 48)	
DC bus voltage	560 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	1.38 ms
Rated voltage	269 V AC (rms)	Thermal time constant	21 min
Rated power	635 W	Rotor inertia	0.31 kgcm ²
Rated speed	6000 rpm	Protection	IP64
Rated torque	1.01 Nm	Color	RAL 9005
Rated current	1.99 A (rms)	Cooling	Convection
Peak torque	3.45 Nm	Motor-only mass	2 kg
Peak current	7.8 A (rms)	Max. axial force 20kh	45 N
Stall torque	1.15 Nm	Max. radial force 20kh	237 N*
Stall current	1.78 A (rms)	Max. axial force 100kh	26 N
No load speed	9680 rpm	Max. radial force 100kh	139 N*
EMF constant ±10%	39 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	0.65 Nm / A (rms)	Sensors	
Torque constant ±10% @ rated load	0.51 Nm / A (rms)	Temperature	PT1000 {PT1000}
Number of poles	10	Feedback	EEM37 (HDSL) multi-turn, 17+12 bits
Electrical time constant	2.15 ms	Brake	
Winding terminal resistance	10.71 Ω	Braking torque	4.50 Nm
Rotary field terminal inductance	23 mH	Voltage	24 V DC
Customs info		Power @20°C	12.0 W
HS Code	85015100	Current @20°C	0.50 A
		Inertia	0.20 kgcm ²
		Mass	0.47 kg



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

