



Engineering data (WIN 783)		Mechanical data (setting 48)	
DC bus voltage	36 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	25 V AC (rms)	Mech. time constant	0.99 ms
Rated voltage	18 V AC (rms)	Thermal time constant	23 min
Rated power	209 W	Rotor inertia	0.55 kgcm ²
Rated speed	1000 rpm	Protection	IP64
Rated torque	2.00 Nm	Color	RAL 9005
Rated current	11.02 A (rms)	Cooling	Convection
Peak torque	6.15 Nm	Motor-only mass	2 kg
Peak current	41.9 A (rms)	Max. axial force 20kh	90 N
Stall torque	2.05 Nm	Max. radial force 20kh	472 N*
Stall current	10.3 A (rms)	Max. axial force 100kh	52 N
No load speed	2060 rpm	Max. radial force 100kh	276 N*
EMF constant ±10%	12 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	0.2 Nm / A (rms)		
Torque constant ±10% @ rated load	0.2 Nm / A (rms)	Sensors Temperature PT1000 {PT1000} Feedback EKM36 (HDSL) multi-turn, 18+12 bits, SIL2	
Number of poles	10		
Electrical time constant	2.44 ms		
Winding terminal resistance	0.41 Ω		
Rotary field terminal inductance	1 mH		
Customs info			
HS Code	85015100		



EGA201N00000800000

M15, 9 poles, rotary



Connector 1 (304)

A	U
B	V
C	W
PE	PE
1	Brake+
2	Brake-
3	+Us/DSL+
4	GND/DSL-

