


Engineering data (WIN 704)		Mechanical data (setting 48)	
DC bus voltage	320 V DC	Max mechanical speed	12000 rpm
Nominal AC voltage	220 V AC (rms)	Mech. time constant	0.92 ms
Rated voltage	153 V AC (rms)	Thermal time constant	23 min
Rated power	597 W	Rotor inertia	0.55 kgcm ²
Rated speed	3000 rpm	Protection	IP64
Rated torque	1.90 Nm	Color	RAL 9005
Rated current	3.06 A (rms)	Cooling	Convection
Peak torque	6.15 Nm	Motor-only mass	2.5 kg
Peak current	12.7 A (rms)	Max. axial force 20kh	64 N
Stall torque	2.05 Nm	Max. radial force 20kh	335 N*
Stall current	2.79 A (rms)	Max. axial force 100kh	37 N
No load speed	4920 rpm	Max. radial force 100kh	196 N*
EMF constant ±10%	44.5 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	0.74 Nm / A (rms)	Sensors	
Torque constant ±10% @ rated load	0.62 Nm / A (rms)	Temperature	PT1000 {PT1000}
Number of poles	10	Feedback	EDS35 (HDSL) single-turn, 24 bits
Electrical time constant	2.53 ms	Brake	
Winding terminal resistance	5.26 Ω	Braking torque	4.50 Nm
Rotary field terminal inductance	13.3 mH	Voltage	24 V DC
Customs info		Power @20°C	12.0 W
HS Code	85015100	Current @20°C	0.50 A
		Inertia	0.20 kgcm ²
		Mass	0.47 kg



EGA201N00000800000

M15, 9 poles, rotary



Connector 1 (304)

A	U
B	V
C	W
PE	PE
1	Brake+
2	Brake-
3	+Us/DSL+
4	GND/DSL-

