

Engineering data (WIN 954)

DC bus voltage	560 V DC
Nominal AC voltage	380 V AC (rms)
Rated voltage	310 V AC (rms)
Rated power	1.2 kW
Rated speed	3000 rpm
Rated torque	3.70 Nm
Rated current	2.6 A (rms)
Peak torque	14.4 Nm
Peak current	10.1 A (rms)
Stall torque	4.8 Nm
Stall current	2.82 A (rms)
No load speed	3680 rpm
EMF constant ±10%	103 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	1.7 Nm / A (rms)
Torque constant ±10% @ rated load	1.4 Nm / A (rms)
Number of poles	10
Electrical time constant	3.01 ms
Winding terminal resistance	7.53 Ω
Rotary field terminal inductance	22.7 mH

Customs info

HS Code	85015220
---------	----------


Mechanical data (setting 48)

Max mechanical speed	12000 rpm
Mech. time constant	0.68 ms
Thermal time constant	30 min
Rotor inertia	1.52 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	3.8 kg
Max. axial force 20kh	75 N
Max. radial force 20kh	392 N*
Max. axial force 100kh	44 N
Max. radial force 100kh	229 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EEM37 (HDSL) multi-turn, 17+12 bits


EGA201N00000800000

M15, 9 poles, rotary


Connector 1 (304)

A	U
B	V
C	W
PE	PE
1	Brake+
2	Brake-
3	+Us/DSL+
4	GND/DSL-

