

Engineering data (WIN 708)

DC bus voltage	320 V DC
Nominal AC voltage	220 V AC (rms)
Rated voltage	155 V AC (rms)
Rated power	1.3 kW
Rated speed	3000 rpm
Rated torque	4.20 Nm
Rated current	7.01 A (rms)
Peak torque	15.3 Nm
Peak current	31 A (rms)
Stall torque	5.1 Nm
Stall current	6.8 A (rms)
No load speed	4800 rpm
EMF constant ±10%	45.5 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.75 Nm / A (rms)
Torque constant ±10% @ rated load	0.60 Nm / A (rms)
Number of poles	10
Electrical time constant	5.48 ms
Winding terminal resistance	1.24 Ω
Rotary field terminal inductance	6.8 mH

Customs info

HS Code	85015220
---------	----------


Mechanical data (setting 48)

Max mechanical speed	9000 rpm
Mech. time constant	0.77 ms
Thermal time constant	25 min
Rotor inertia	2.04 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	3.8 kg
Max. axial force 20kh	113 N
Max. radial force 20kh	595 N*
Max. axial force 100kh	66 N
Max. radial force 100kh	348 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EDS35 (HDSL) single-turn, 24 bits


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

