



Engineering data (WIN 829)		Mechanical data (setting 48)	
DC bus voltage	320 V DC	Max mechanical speed	9000 rpm
Nominal AC voltage	220 V AC (rms)	Mech. time constant	0.61 ms
Rated voltage	172 V AC (rms)	Thermal time constant	40 min
Rated power	2.8 kW	Rotor inertia	5.7 kgcm ²
Rated speed	3000 rpm	Protection	IP64
Rated torque	8.80 Nm	Color	RAL 9005
Rated current	11.42 A (rms)	Cooling	Convection
Peak torque	33.9 Nm	Motor-only mass	4.7 kg
Peak current	43.1 A (rms)	Max. axial force 20kh	135 N
Stall torque	11.3 Nm	Max. radial force 20kh	713 N*
Stall current	11.6 A (rms)	Max. axial force 100kh	79 N
No load speed	3720 rpm	Max. radial force 100kh	417 N*
EMF constant ±10%	59 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	0.98 Nm / A (rms)	Sensors	
Torque constant ±10% @ rated load	0.77 Nm / A (rms)	Temperature	PT1000 {PT1000}
Number of poles	10	Feedback	EKM36 (HDSL) multi-turn, 18+12 bits, SIL2
Electrical time constant	6.27 ms	Brake	
Winding terminal resistance	0.59 Ω	Braking torque	9.00 Nm
Rotary field terminal inductance	3.7 mH	Voltage	24 V DC
Customs info		Power @20°C	18.0 W
HS Code	85015220	Current @20°C	0.75 A
		Inertia	0.60 kgcm ²
		Mass	0.82 kg



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

