

Engineering data (WIN 829)

DC bus voltage	320 V DC
Nominal AC voltage	220 V AC (rms)
Rated voltage	172 V AC (rms)
Rated power	2.8 kW
Rated speed	3000 rpm
Rated torque	8.80 Nm
Rated current	11.42 A (rms)
Peak torque	33.9 Nm
Peak current	43.1 A (rms)
Stall torque	11.3 Nm
Stall current	11.6 A (rms)
No load speed	3720 rpm
EMF constant ±10%	59 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.98 Nm / A (rms)
Torque constant ±10% @ rated load	0.77 Nm / A (rms)
Number of poles	10
Electrical time constant	6.27 ms
Winding terminal resistance	0.59 Ω
Rotary field terminal inductance	3.7 mH

Customs info

HS Code	85015220
---------	----------


Mechanical data (setting 48)

Max mechanical speed	9000 rpm
Mech. time constant	0.61 ms
Thermal time constant	40 min
Rotor inertia	5.7 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	6.4 kg
Max. axial force 20kh	135 N
Max. radial force 20kh	713 N*
Max. axial force 100kh	79 N
Max. radial force 100kh	417 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EKM36 (HDSL) multi-turn, 18+12 bits, SIL2



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

