



Engineering data (WIN 713)		Mechanical data (setting 48)	
DC bus voltage	560 V DC	Max mechanical speed	9000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	0.60 ms
Rated voltage	289 V AC (rms)	Thermal time constant	35 min
Rated power	2.4 kW	Rotor inertia	4.49 kgcm ²
Rated speed	3000 rpm	Protection	IP64
Rated torque	7.70 Nm	Color	RAL 9005
Rated current	6.03 A (rms)	Cooling	Convection
Peak torque	28.8 Nm	Motor-only mass	4.7 kg
Peak current	27.4 A (rms)	Max. axial force 20kh	131 N
Stall torque	9.6 Nm	Max. radial force 20kh	691 N*
Stall current	6 A (rms)	Max. axial force 100kh	77 N
No load speed	3910 rpm	Max. radial force 100kh	404 N*
EMF constant ±10%	97 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	1.6 Nm / A (rms)		
Torque constant ±10% @ rated load	1.3 Nm / A (rms)		
Number of poles	10		
Electrical time constant	6.01 ms		
Winding terminal resistance	1.98 Ω		
Rotary field terminal inductance	11.9 mH		
Customs info		Sensors	
HS Code	85015220	Temperature	PT1000 {PT1000}
		Feedback	EKM36 (HDSL) multi-turn, 17 + 12 bits
		Brake	
		Braking torque	9.00 Nm
		Voltage	24 V DC
		Power @20°C	18.0 W
		Current @20°C	0.75 A
		Inertia	0.60 kgcm ²
		Mass	0.82 kg


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

