


Engineering data (WIN 728)		Mechanical data (setting 48)							
DC bus voltage	320 V DC	Max mechanical speed	9000 rpm						
Nominal AC voltage	220 V AC (rms)	Mech. time constant	0.81 ms						
Rated voltage	164 V AC (rms)	Thermal time constant	45 min						
Rated power	3.3 kW	Rotor inertia	7.9 kgcm²						
Rated speed	3000 rpm	Protection	IP64						
Rated torque	10.50 Nm	Color	RAL 9005						
Rated current	14.73 A (rms)	Cooling	Convection						
Peak torque	36 Nm	Motor-only mass	11.2 kg						
Peak current	52.5 A (rms)	Max. axial force 20kh	126 N						
Stall torque	12 Nm	Max. radial force 20kh	665 N*						
Stall current	14.2 A (rms)	Max. axial force 100kh	74 N						
No load speed	4310 rpm	Max. radial force 100kh	389 N*						
EMF constant ±10%	51 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length							
Theoretical torque constant ±10%	0.84 Nm / A (rms)								
Torque constant ±10% @ rated load	0.71 Nm / A (rms)	<table><tr><th colspan="2">Sensors</th></tr><tr><td>Temperature</td><td>PT1000 {PT1000}</td></tr><tr><td>Feedback</td><td>EKS36 (HDSL) single-turn, 17 bits</td></tr></table>		Sensors		Temperature	PT1000 {PT1000}	Feedback	EKS36 (HDSL) single-turn, 17 bits
Sensors									
Temperature	PT1000 {PT1000}								
Feedback	EKS36 (HDSL) single-turn, 17 bits								
Number of poles	10								
Electrical time constant	8.10 ms								
Winding terminal resistance	0.42 Ω								
Rotary field terminal inductance	3.4 mH								
Customs info									
HS Code	85015220								


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

