

Engineering data (WIN 977)

DC bus voltage	320 V DC
Nominal AC voltage	220 V AC (rms)
Rated voltage	185 V AC (rms)
Rated power	6.3 kW
Rated speed	3000 rpm
Rated torque	20.00 Nm
Rated current	22.97 A (rms)
Peak torque	72 Nm
Peak current	76.6 A (rms)
Stall torque	24 Nm
Stall current	22.3 A (rms)
No load speed	3380 rpm
EMF constant ±10%	65 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	1.08 Nm / A (rms)
Torque constant ±10% @ rated load	0.87 Nm / A (rms)
Number of poles	10
Electrical time constant	9.09 ms
Winding terminal resistance	0.22 Ω
Rotary field terminal inductance	2 mH

Customs info

HS Code	85015220
---------	----------

Mechanical data (setting 48)

Max mechanical speed	9000 rpm
Mech. time constant	0.62 ms
Thermal time constant	75 min
Rotor inertia	18.7 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	11.2 kg
Max. axial force 20kh	147 N
Max. radial force 20kh	775 N*
Max. axial force 100kh	86 N
Max. radial force 100kh	453 N*


* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EKS36 (HDSL) single-turn, 18 bits, SIL2

Brake

Braking torque	18.00 Nm
Voltage	24 V DC
Power @20°C	24.0 W
Current @20°C	1.00 A
Inertia	2.00 kgcm ²
Mass	1.80 kg



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

