

Engineering data (WIN 728)

DC bus voltage	320 V DC
Nominal AC voltage	220 V AC (rms)
Rated voltage	164 V AC (rms)
Rated power	3.3 kW
Rated speed	3000 rpm
Rated torque	10.50 Nm
Rated current	14.73 A (rms)
Peak torque	36 Nm
Peak current	52.5 A (rms)
Stall torque	12 Nm
Stall current	14.2 A (rms)
No load speed	4310 rpm
EMF constant ±10%	51 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	0.84 Nm / A (rms)
Torque constant ±10% @ rated load	0.71 Nm / A (rms)
Number of poles	10
Electrical time constant	8.10 ms
Winding terminal resistance	0.42 Ω
Rotary field terminal inductance	3.4 mH

Customs info

HS Code	85015220
---------	----------


Mechanical data (setting 48)

Max mechanical speed	9000 rpm
Mech. time constant	0.81 ms
Thermal time constant	45 min
Rotor inertia	7.9 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	11.2 kg
Max. axial force 20kh	126 N
Max. radial force 20kh	665 N*
Max. axial force 100kh	74 N
Max. radial force 100kh	389 N*

* Defined for point of action at ½ output shaft length

Sensors

Temperature	PT1000 {PT1000}
Feedback	EKM36 (HDSL) multi-turn, 18+12 bits, SIL2


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

