


Engineering data (WIN 732)		Mechanical data (setting 48)	
DC bus voltage	320 V DC	Max mechanical speed	9000 rpm
Nominal AC voltage	220 V AC (rms)	Mech. time constant	0.64 ms
Rated voltage	165 V AC (rms)	Thermal time constant	65 min
Rated power	2.8 kW	Rotor inertia	15.1 kgcm ²
Rated speed	1500 rpm	Protection	IP64
Rated torque	18.00 Nm	Color	RAL 9005
Rated current	11.81 A (rms)	Cooling	Convection
Peak torque	60 Nm	Motor-only mass	11.2 kg
Peak current	39.8 A (rms)	Max. axial force 20kh	180 N
Stall torque	20 Nm	Max. radial force 20kh	950 N*
Stall current	11.6 A (rms)	Max. axial force 100kh	106 N
No load speed	2110 rpm	Max. radial force 100kh	555 N*
EMF constant ±10%	104 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	1.72 Nm / A (rms)		
Torque constant ±10% @ rated load	1.52 Nm / A (rms)		
Number of poles	10	Sensors	
Electrical time constant	8.75 ms	Temperature	PT1000 {PT1000}
Winding terminal resistance	0.72 Ω	Feedback	EKS36 (HDSL) single-turn, 18 bits, SIL2
Rotary field terminal inductance	6.3 mH	Brake	
Customs info		Braking torque	18.00 Nm
HS Code	85015220	Voltage	24 V DC
		Power @20°C	24.0 W
		Current @20°C	1.00 A
		Inertia	2.00 kgcm ²
		Mass	1.80 kg



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

