


Engineering data (WIN 880)		Mechanical data (setting 48)	
DC bus voltage	560 V DC	Max mechanical speed	6000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	0.73 ms
Rated voltage	274 V AC (rms)	Thermal time constant	47 min
Rated power	4.2 kW	Rotor inertia	25.6 kgcm ²
Rated speed	2000 rpm	Protection	IP64
Rated torque	20.00 Nm	Color	RAL 9005
Rated current	10.66 A (rms)	Cooling	Convection
Peak torque	72 Nm	Motor-only mass	9.2 kg
Peak current	42.3 A (rms)	Max. axial force 20kh	156 N
Stall torque	24 Nm	Max. radial force 20kh	822 N*
Stall current	10.8 A (rms)	Max. axial force 100kh	91 N
No load speed	2830 rpm	Max. radial force 100kh	480 N*
EMF constant ±10%	134 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	2.22 Nm / A (rms)	Sensors	
Torque constant ±10% @ rated load	1.88 Nm / A (rms)	Temperature	PT1000 {PT1000}
Number of poles	10	Feedback	EKS36 (HDSL) single-turn, 17 bits
Electrical time constant	13.33 ms	Brake	
Winding terminal resistance	0.81 Ω	Braking torque	36.00 Nm
Rotary field terminal inductance	10.8 mH	Voltage	24 V DC
Customs info		Power @20°C	26.0 W
HS Code	85015220	Current @20°C	1.08 A
		Inertia	6.20 kgcm ²
		Mass	2.85 kg


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

