


Engineering data (WIN 932)		Mechanical data (setting 48)	
DC bus voltage	560 V DC	Max mechanical speed	6000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	0.74 ms
Rated voltage	269 V AC (rms)	Thermal time constant	47 min
Rated power	5.3 kW	Rotor inertia	25.6 kgcm ²
Rated speed	3000 rpm	Protection	IP64
Rated torque	17.00 Nm	Color	RAL 9005
Rated current	13.81 A (rms)	Cooling	Convection
Peak torque	72 Nm	Motor-only mass	18 kg
Peak current	59.6 A (rms)	Max. axial force 20kh	136 N
Stall torque	24 Nm	Max. radial force 20kh	718 N*
Stall current	15.3 A (rms)	Max. axial force 100kh	80 N
No load speed	4000 rpm	Max. radial force 100kh	420 N*
EMF constant ±10%	95 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	1.57 Nm / A (rms)	Sensors	
Torque constant ±10% @ rated load	1.23 Nm / A (rms)	Temperature	PT1000 {PT1000}
Number of poles	10	Feedback	EDS35 (HDSL) single-turn, 24 bits
Electrical time constant	13.41 ms	Brake	
Winding terminal resistance	0.41 Ω	Braking torque	36.00 Nm
Rotary field terminal inductance	5.5 mH	Voltage	24 V DC
Customs info		Power @20°C	26.0 W
HS Code	85015220	Current @20°C	1.08 A
		Inertia	6.20 kgcm ²
		Mass	2.85 kg



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

