


Engineering data (WIN 932)		Mechanical data (setting 48)	
DC bus voltage	560 V DC	Max mechanical speed	6000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	0.74 ms
Rated voltage	269 V AC (rms)	Thermal time constant	47 min
Rated power	5.3 kW	Rotor inertia	25.6 kgcm ²
Rated speed	3000 rpm	Protection	IP64
Rated torque	17.00 Nm	Color	RAL 9005
Rated current	13.81 A (rms)	Cooling	Convection
Peak torque	72 Nm	Motor-only mass	13.8 kg
Peak current	59.6 A (rms)	Max. axial force 20kh	130 N
Stall torque	24 Nm	Max. radial force 20kh	684 N*
Stall current	15.3 A (rms)	Max. axial force 100kh	76 N
No load speed	4000 rpm	Max. radial force 100kh	400 N*
EMF constant ±10%	95 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	1.57 Nm / A (rms)		
Torque constant ±10% @ rated load	1.23 Nm / A (rms)	Sensors Temperature PT1000 {PT1000} Feedback EDS35 (HDSL) single-turn, 24 bits	
Number of poles	10		
Electrical time constant	13.41 ms		
Winding terminal resistance	0.41 Ω		
Rotary field terminal inductance	5.5 mH		
Customs info			
HS Code	85015220		



BGC110N00001216000

M23, 8 poles, rotary



Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

