

Engineering data (WIN 993)

DC bus voltage	560 V DC
Nominal AC voltage	380 V AC (rms)
Rated voltage	284 V AC (rms)
Rated power	6.6 kW
Rated speed	3000 rpm
Rated torque	21.00 Nm
Rated current	16.19 A (rms)
Peak torque	90 Nm
Peak current	63.9 A (rms)
Stall torque	30 Nm
Stall current	17.8 A (rms)
No load speed	3720 rpm
EMF constant ±10%	102 V AC (rms) / 1000rpm
Theoretical torque constant ±10%	1.69 Nm / A (rms)
Torque constant ±10% @ rated load	1.30 Nm / A (rms)
Number of poles	10
Electrical time constant	14.24 ms
Winding terminal resistance	0.33 Ω
Rotary field terminal inductance	4.7 mH

Customs info

HS Code	85015220
---------	----------


Mechanical data (setting 48)

Max mechanical speed	6000 rpm
Mech. time constant	0.66 ms
Thermal time constant	52 min
Rotor inertia	32.7 kgcm ²
Protection	IP64
Color	RAL 9005
Cooling	Convection
Motor-only mass	13.8 kg
Max. axial force 20kh	136 N
Max. radial force 20kh	717 N*
Max. axial force 100kh	80 N
Max. radial force 100kh	419 N*

** Defined for point of action at ½ output shaft length*

Sensors

Temperature	PT1000 {PT1000}
Feedback	EDM35 (HDSL) multi-turn, 20+12 bits


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

