


Engineering data (WIN 1068)		Mechanical data (setting 48)	
DC bus voltage	560 V DC	Max mechanical speed	6000 rpm
Nominal AC voltage	380 V AC (rms)	Mech. time constant	0.61 ms
Rated voltage	308 V AC (rms)	Thermal time constant	62 min
Rated power	7.6 kW	Rotor inertia	47 kgcm²
Rated speed	2000 rpm	Protection	IP64
Rated torque	36.50 Nm	Color	RAL 9005
Rated current	17.31 A (rms)	Cooling	Convection
Peak torque	132 Nm	Motor-only mass	13.8 kg
Peak current	63.7 A (rms)	Max. axial force 20kh	165 N
Stall torque	44 Nm	Max. radial force 20kh	871 N*
Stall current	17.7 A (rms)	Max. axial force 100kh	97 N
No load speed	2530 rpm	Max. radial force 100kh	509 N*
EMF constant ±10%	154 V AC (rms) / 1000rpm	* Defined for point of action at ½ output shaft length	
Theoretical torque constant ±10%	2.547 Nm / A (rms)		
Torque constant ±10% @ rated load	2.109 Nm / A (rms)	Sensors	
Number of poles	10	Temperature	PT1000 {PT1000}
Electrical time constant	14.29 ms	Feedback	EDS35 (HDSL) single-turn, 24 bits
Winding terminal resistance	0.49 Ω		
Rotary field terminal inductance	7 mH		

Customs info	
HS Code	85015230


BGC110N00001216000

M23, 8 poles, rotary


Connector 1 (283)

1	U
4	V
3	W
2	PE
A	Brake+
B	Brake-
C	GND/DSL-
D	+Us/DSL+

